TECHMAIL

GEN II BACK MOUNT

Float and Extension Options

6507 1.75 Horizontal

5453SA Vertical

Extensions

Standard Float PVC

316SS6 Float

Code	Description	Spring
CMTL6	6” Extension	6547
CMTL12	12” Extension	6547L
CMTL18	18" Extension	6547L

20” Float

3” Float

Code	Description	Spring
CMUL6	6” Extension	6547L
CMUL12	12" Extension	6547X
CMUL18	18" Extension	6547X

Elastomer Options

-15F to 350F use standard Viton
32F to 450F use Aflas

Body Options

Part No.	Description
5528BM	2” NPT
5443BM	2” NPT SS6
5548BM	2” Grooved
5562BM	2” 150 RF Flanged
5563BM	2” 300 RF Flanged
5564BM	2” 600 RF Flanged
5565BM	2” 900 RF Flanged
5566BM	2” 150 RTJ Flanged
5567BM	2” 300 RTJ Flanged
5568BM	2” 600 RTJ Flanged
5569BM	2” 1500 RTJ Flanged
5570BM	3” 150 RF Flanged
5555BM	3” 300 RF Flanged
5571BM	3” 600 RF Flanged
5572BM	3” 900 RF Flanged
5556BM	3” 1500 RF Flanged
5573BM	3” 600 RTJ Flanged
5574BM	3” 900 RTJ Flanged
5575BM	4” 150 RF Flanged
5575EBBM	4” 150 RF Flanged Enduro Bond
5576BM	4” 300 RF Flanged
5577BM	4” 600 RF Flanged
5578BM	4” 600 RTJ Flanged
5579BM	4” 1500 RF Flanged
5579EBBM	4” 1500RF Flanged Enduro Bond
5580BM	6” 1500 RF Flanged
5580EBBM	6” 1500 RF Flanged Enduro Bond
5558BM + 1674N	3” HU W/O Sight Glass UN Thread
5550BM + 2734	4” HU W/Sight Glass ACME Thread
5550BM + 2901	4” HU W/Sight Glass UN Thread
5551BM + 2734	4” HU W/O Sight Glass ACME Thread
5551BM + 2901	4” HU W/O Sight Glass UN Thread
5549BM + 2736	5” HU W/Sight Glass UN Thread
5552BM + 2736	5” HU W/O Sight Glass UN Thread

Float Options

Part Number	Description	Temp	Pressure	Spring
6562A	Standard PVC	200	4000 psi	Standard
5461SS6	316 Stainless	500F	2000psi	Standard
6606A	3” float	200F	4000 psi	Heavy
6611A	20” long	200F	4000 psi	Heavy

Note: 3” and 20” floats used for interface application.

Tech Mail No. 39 September 10, 2009
Kimray, Inc. Oklahoma City, Oklahoma